




Technical information (06/2022)

GRAVIHEL PRIMER FILLER QDry SPRAY





- Shake a can for 3 minutes and test the paint on a test surface.
- Spray in several thin coats, from distance of approx. 25 cm.
- The drying time depend on the type of paint, thickness of a coat and temperature.
- Color shade: gray
- Appearance: matt
- VOC compliant

SUBSTRATE PREPARATION	
	 P220 – P280
	 GRAVIHEL Antisilicone cleaner

VOC

2004/42/II B(e) (840) 839

EU limit value VOC for this type of product (category II B (e)) in the form, which is ready for application is 840 g/l. VOC of this product, prepared for use is 839 g/l.

		Clean the surface to be painted thoroughly with GRAVIHEL silicone cleaner. The area must be dry and free of dust and grease
	Shaking:	Shake can vigorously for 3 minutes
	Application:	Spray in several thin coats, from distance of approx. 25 cm.
	Drying time:	The drying time depends on the type of paint, thickness of a coat and temperature.

GRAVI HEL

	Shelf life:	5 years
---	--------------------	---------

FOR PROFESSIONAL USE ONLY - See Safety Data Sheet

Contains: acetone, butan-1-ol. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with regional regulations. Buildup of explosive mixtures possible without sufficient ventilation.