








Technical information (06/2022)

## GRAVIHEL 1K RMS SPRAY


- Shake a can for 3 minutes and test the paint on a test surface.
- Spray in several thin coats, from distance of approx. 25 cm.
- The drying time depend on the type of paint, thickness of a coat and temperature.
- Color shade: RAL, gold effect, chrome effect
- Appearance: High gloss, matt
- VOC compliant

<b>SUBSTRATE PREPARATION</b>	<b>GRAVIHEL 1K PRIMER or 2K PRIMER or old enamel</b>
	 P360 – P600
	 GRAVIHEL Antisilicone cleaner

**VOC** 2004/42/II B(e) (840) 839  
 EU limit value VOC for this type of product (category II B (e)) in the form, which is ready for application is 840 g/l. VOC of this product, prepared for use is 839 g/l.

		Clean the surface to be painted thoroughly with GRAVIHEL silicone cleaner. The area must be dry and free of dust and grease
	<b>Shaking:</b>	Shake can vigorously for 3 minutes
	<b>Colour test:</b>	The colour should be applied on to a piece of test cardboard to assess its suitability prior to application on the object
	<b>Application:</b>	Spray in several thin coats, from distance of approx. 25 cm.
	<b>Drying time:</b>	The drying time depends on the type of paint, thickness of a coat and temperature.

# GRAVI HEL

	<b>Shelf life:</b>	5 years
---	--------------------	---------

FOR PROFESSIONAL USE ONLY - See Safety Data Sheet

Contains: acetone, butan-1-ol. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with regional regulations. Buildup of explosive mixtures possible without sufficient ventilation.